



Collection: MARGAUX

Finish*:



NF - Neutral

Main features:



Consumer benefits

- Leaking avoided due to perfect seal provided by box's plastic envelope
- Metal body in de-zinc resistant brass, guaranteeing no porosity or cracking, for a perfect seal
- Easy maintenance: direct access to valve servicing parts by removing trim
- Option to switch from mechanical to thermostatic mode, thanks to easy valve and trim change

Installation benefits

- Suits a wide range of trims
- Integrated level: easy box positioning
- Can be installed on different surfaces: walls in concrete, plaster, wood, industrial partitions, etc.
- Box cover with prongs to use as cutout template
- Connector available to annex two Modulo universal boxes, for perfect, esthetic alignment

Features

- Weight: 2 kg
- Designed to receive single
- Suits a wide range of trims
- Inside connection thread G 1/2"
- Integrated level for easy adjustment during installation
- Prongs that mark the dry wall for cutting (cutting template)
- Soundproofing installation by a rubber
- DZR brass (dezincification resistant brass)
- Installation: Built-in
- lever mixers, thermostatic valves, diverters
- Seal flange
- Plug G 1/2"
- Installation bracket
- Water switch for water flush and hydro pressure testing
- cushioned brass construction

Optional products

- 98701D: Adjustment kit
- 98700D: Kit to install 1-handle trim on thin wall
- 98788D: Box connector to align 2 superposed boxes(chromed brass)
- 98789D: Kit to install 2-handle trim on thin wall

Technical drawing

